

Contiguous Points of Delivery, Version 12

Effective: TBD

~~The Contiguous Point(s) of Delivery (POD) criteria applies only to Point-to-Point (PTP) transmission service. It relates to treatment of a set of individual PODs as one contiguous POD in a PTP transmission service agreement at the request of the Transmission. In order for Contiguous PODs to be agreed to by BPAT, the criteria spelled out below must be met. This Business Practice is applicable to all BPA Transmission Customers and offers further clarification of the BPA OATT and General rate Schedule Provisions.~~

This Business Practice describes the criteria for a Contiguous Point of Delivery (POD).

Table of Contents

A. Contiguous Points of Delivery/POD General Criteria

B. Contiguous POD Criteria

A.C. Requesting a Contiguous POD

A. Contiguous Point of Delivery/POD General Criteria

~~1. The Transmission Customer's designated contiguous points of delivery are subject to the following terms:~~

1. The Contiguous POD criteria applies only to Point-to-Point (PTP) transmission service.

~~2. A Contiguous POD is a set of individual PODs sharing a common boundary or service area that are aggregated and treated as a single POD in a PTP TSR. ~~treated as one contiguous POD in a PTP transmission service agreement submitted through a TSR.~~~~

B. Contiguous POD Criteria

In order for Contiguous PODs to be agreed to by BPAT, the criteria below must be met:

1. All PODs on the delivery side must be interconnected through a transmission or distribution system. If the Customer's system is operated normally open, the Customer and BPA will agree to an operating plan for any load shifting between and/or among PODs in the contiguous set to prevent adverse impacts on the reliability of the Federal Columbia River Transmission System (FCRTS). The PODs must be significantly interconnected electrically on both high side and low side.
2. In the event of an credible outage, each POD within the contiguous set must be capable of providing electric backup service to any other POD of that contiguous set so that retail Customers within the load center served by the contiguous set of

PODs realize no interruption in service. However, if a substation or interconnection serves two or more PODs at different voltage levels and the source is a single transmission line, the PODs may be considered contiguous if there are reasonable technical and/or historical basis for doing so.

3. All PODs in the set of contiguous PODs must be located on the same side of a constraint or potential constraint. Shifts in loads from one POD to another POD in the contiguous set may not adversely affect any constraint, such as those posted on BPA's Open Access Same-Time Information System (OASIS).
4. The Transmission Customer may not direct BPA Transmission Services to deliver a specific amount of demand to a specific POD within the contiguous set of PODs. BPA Transmission Services has no obligation to deliver specific amounts to ~~individual the~~ delivery points that constitute the contiguous set of PODs. ~~BPA Transmission Services has no obligation to construct new facilities at or between PODs.~~ BPA Transmission Services has no obligation to construct new facilities at or between PODs included in the contiguous set of PODs as long as BPA Transmission Services can deliver the combined demands to the contiguous sets of PODs
5. All PODs within the contiguous set of PODs must be in a single ~~Control Area~~ **Balancing Authority Area (BAA)**.
6. All PODs associated with the Southern Intertie are specifically excluded from consideration as part of a contiguous set of PODs. ~~(-Big Eddy, John Day, California-Oregon Border, and Nevada-Oregon Border)-are independent PODs.~~
7. The utility requesting contiguous PODs must be capable of receiving electric service at each of the PODs in the contiguous set. If the utility is requesting contiguous PODs to deliver to a third party, then that third party must be capable of receiving delivery at each of the PODs in the contiguous set.
8. Where appropriate, the Customer must agree to use limits on the individual PODs included in the contiguous set of PODs.
9. Contiguous PODs are granted for real power only. ~~Issues associated with Reactive Power will be covered by separate procedures~~
10. These criteria shall be reviewed ~~annually as needed~~. An individual Customer's situation shall be reviewed if there are any changes in how its system is served or impacted by any transmission system conditions. ~~The Customer must notify their BPA Account Executive prior to a change.~~ BPA Transmission Services reserves the right to modify any characteristics of a Customer's contiguous POD if changes in a system ~~(BPA, Customer, third-party)~~ warrant such modification.

C. Requesting a Contiguous POD

1. A BPA PTP Customer who wants BPA to consider adding a new Contiguous POD or make changes to an existing Contiguous POD in their PTP Agreement must contact their Transmission Account Executive in writing.

B. Additional Information

Version History

Version 2	Xx/xx/16 Reviewed and updated content.
Version 1	10/01/01 New business practice.

